

FUJINON

Ver1.2

| | | Ver1.2 | |
|--------------------------|--------------------------------------|----------------------|--|
| 型番 | Product Name | CF35ZA-1S | |
| 焦点距離 [mm] | Focal length [mm] | 35 | |
| | | (34.78) | |
| 絞り範囲 (F no) | Iris range (F. no) | F1.8-F16 | |
| 画角 (H x V) | Angle of view | 23.0° × 17.3° (1.1") | |
| フォーカス範囲 (レンズメカ先端より) [mm] | Working distance | ∞ - 200 | |
| | (from front of lens barrel) [mm] | ∞ - 200 | |
| 操作方法:フォーカス | Operation of focus | Manual | |
| 操作方法:アイリス | Operation of iris | Manual | |
| フィルタ径 [mm] | Filter thread [mm] | M37.5 x 0.5 | |
| マウント | Mount | C-mount | |
| 質量 (約) [g] | Weight (approx.) [g] | 165g | |
| 適合センサーサイズ (最大) | Sensor size (max.) | 1.1" (2.5µm) | |
| バックフォーカス (空気換算長) [mm] | Back focal distance (in air) [mm] | 21.30 | |
| フランジバック [mm] | Flange back [mm] | 17.526 | |
| 入射瞳位置 (マウント面から) [mm] | Entrance pupil position | 26.50 | |
| | (from Mount) [mm] | -26.59 | |
| 射出瞳位置 (結像面より) [mm] | Exit pupil position | 102.02 | |
| | (from image plane) [mm] | -102.02 | |
| 前側主点 (マウント面から) | Front principal point (from Mount) | -4.54 | |
| 後側主点 (マウント面から) | Rear principal point (from Mount) | -17.25 | |
| 二点間の距離 (主点間隔) | Distance between the pincipal points | -12.71 | |
| TVディストーション [%] | TV distortion [%] | -0.32 | |
| | Dimension [mm] | φ39 × 67.3 | |
| 主光線入射角 [°] | Chief Ray Angle [°] | 4.53 | |
| 周辺光量 (F 4.0·隅) | Relative illumination [%] | 92 | |
| | (Aperture: F 4.0 | | |
| | Image height: at diagonal) | | |
| 周辺光量 (開放・隅) | Relative illumination [%] | | |
| | (Aperture: at full open, | 37 | |
| | Image height: at diagonal) | | |
| 使用温度範囲 | Operation Temperature | -10℃ ~ +50℃ | |