











iVS-CV28P

Unlock the full potential of vision data for your application.

Embedded, modular, cloud-connected, and secure - iENSO develops and delivers vision systems for any application.

Key features:

- Dual-core Arm ®Cortex®-A53 up to 1 GHz
- Up to 4Kp30 maximum encoding performance
- CNN / DNN inference acceleration for detection, classification, and more
- +320 MPixel/s input rate
- Multi exposure HDR and 3-axis image stabilization

- 180° fisheve lens distortion correction
- Single or dual sensor input with independent ISP configuration
- H.265/HVEC, H.264, MJPEG encoding
- Support for 16-bit LPDDR4(x) / DDR4
- Secure boot with TrustZone® and secure
- Broad image sensor support
- Based on 10nm low-power CMOS process

Sellis	process			
Senson 2 Connector	Block Diagram			Wi-Fi + BLE
Şensci 2 Konnector	Image Signal Processor (ISP)	Dual-Core ARM® CORTEX A53 NEON FPU Extension	Computer Vision Processor CVFlow™	Module
ALS/IRC Connector	System Peripherals Timers, UART, JTAG, SPI, RTC, I2C, I2S, GPIO, PWM, ADC	Memory LPDDR4 / DDR4 16-Bit SPI NAND	Video CODEC AVC/HVEC/MJPEG Multi-CH, Encode	POE Module Connector LTE Module Connector
PIR/Motion Connector	Interfaces/Inputs MIPI CSI-2, PIR, ALS,	Security Features Secure Boot – Trust Zone®, TRNG, OTP,	Connectivity USB 2.0, SDI/SDIO, Ethernet, LED	Micro SD Connector
MIC Connector	Mic	DRAM Scrambling and DRAM Virtualization	illumination, Speaker	Speaker Conn LED Out Conn



Give your vision the edge

- Application-based turnkey embedded vision solutions
- · Edge AI for powerful on-device decision-making
- Flexible Cloud platform and end-to-end security

HARDWARE SPECIFICATIONS - iVS-CV28P

Ambarella CV28 Based Vision SoC

Processor

- Dual-core Arm® Cortex®-A53 up to 1 GHz
- NEON™ SIMD and FPU acceleration
- 10 nm low-power CMOS

Sensor I/O

Advanced

Image Signal

Processing

- MIPI CSI-2, sLVDS, SLVS
- · 2 sensor inputs
- Supports up to 8MP CMOS image sensor
- · Up to 320 Mpixel/s maximum pixel rate
- · Lens shading correction
- Multi-exposure HDR
- 3D motion compensated noise reduction (MCTF)
- 3-Axis Electronic Image Stabilization (EIS)
- · Digital PTZ and Virtual Cameras
- · OSD engine, overlays, privacy mask
- · Crop, mirror, flip, rotation
- · On-chip stitching
- · Geometric lens distortion correction
- · Gamma compensation and color enhancement
- · WDR with local tone mapping

Video Processing

- H.265 / HEVC, H.264, MJPEG
- · Up to 4KP30 encoding performance Dynamic region of interest (ROI)
- · Multiple CBR and VBR rate control modules

AI Power Intelligence **Video Analytics**

- CVFlow® vision processor for CNN / DNN edge analytics · Pre-integrated AI Detectors or provide your own
- · Can utilize models trained with industry-standard tools such as Caffe, TensorFlow or PyTorch

Networking & Connectivity

- Wi-Fi 802.11 (optional)
- BT / BLE (optional) · LTE Module (optional)
- Ethernet PoE Module (optional)

- Audio Codec
- · Line In and Line Out

Memory

Audio

- Up to 8Gb LPDDR4 DRAM
- 4Gb SLC NAND Flash
- · Optional eMMC

Interfaces

- USB 2.0 (Device / Host)
- Micro SD
- · SPI, I2C, JTAG, UART, GPIO, PWM, ADC · LED Flash Control
- Expansion I/O Port: MIPI-DSI, HDMI, GPIO

Security

- AES / SHA1 / SHA2-256 crypto acceleration
- Secure boot with TrustZone® and secure memory, TRNG, OTP, DRAM scrambling and virtualization
 Optional SOC monitoring

Power In

Physical

- Standard Board size 2.5 x 2.5 (inch)
- Custom board size available

Environmental

- Operating temperature: -20°C to 70°C
- Operating humidity: 5% to 90%

os

• Linux

in

Camera Modules

- Sensor Modules up to 8MP/4K
- Multiple lens options
- · IR or white LED illumination options
- · IR Filter for night vision options



SECURITY



PRECISION FARMING



HOME AUTOMATION



SMART APPLIANCES





Additional information:

- Compatible sensor modules (iSM): iENSO.com\ism
- · Custom module versions available upon request

Contact iENSO.com to discuss your specific needs









www.ienso.com

Established in 2003, iENSO provides embedded vision data systems that help global brands turn their products into vision data devices. iENSO provides fully secure end-to-end solutions that capture vision data and process it at the Edge and in the Cloud, giving product companies the opportunity to unlock the business benefits of recurring revenue and data monetization.

Americas

Global HQ Toronto 20 Mural St., Unit 7 Richmond Hill, ON Canada L4B 1K3 (905) 763-6938 • vision@ienso.com Europe

Kyiv, Ukraine • EU@ienso.com

Middle East

Tel Aviv, Israel • ME@ienso.com

Shenzhen, PRC • Asia@ienso.com